

CARTRIDGE ACTUATED DEVICES, INC. 51 Dwight Place, Fairfield, New Jersey 07004

074055 26 AUG 04 page 1 of 3

HAZARDOUS CHEMICAL MATERIAL SAFETY DATA SHEET

(Conforms to the requirements of 29 CFR 1910.1200)

I. PRODUCT IDENTITY: Cartridges, power device, UN0323

1.4S, Pkg. Gr. II

US DOT EX-9609043

(Cartridge Assembly, CAD P/N: 074055,

Fike P/N: 02-4134)

Net Explosive Weight 1.500 grams per unit

CARTRIDGE ACTUATED DEVICES, INC. 24 HOUR EMERGENCY PHONE #

51 Dwight Place IN U.S.A.: **800-424-9300**

Fairfield, N.J. 07004 OUTSIDE U.S.A.:

Telephone Number: 973-575-1312 202-483-7616 CALL COLLECT Prepared by CAD Engineering FIRE, SPILL, EMERGENCY ONLY

Material(s) described is/are: Electro-Pyrotechnic device and by-products of

initiation.

II. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS: N/A

Chemical and common name of Hazardous chemical ingredients:

** COMMON NAME	CAS NO.
Nitroglycerin	000055-63-0
Nitrocellulose	009004-70-0
Potassium Chlorate	003811-04-9
Lead Thiocyanate	000592-87-0

III. PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling point: N/A Solubility in water: N/A Specific gravity: N/A pH: N/D Vapor Pressure: N/D Evaporation Rate: N/A

% Volatile: Negligible.



CARTRIDGE ACTUATED DEVICES, INC. 51 Dwight Place, Fairfield, New Jersey 07004

074055 26 AUG 04 page 2 of 3

IV. FIRE, EXPLOSION AND REACTIVITY HAZARD DATA

<u>DANGER</u>	Extremely FlammableEXPLOSIVE
	Keep away from heat and keep shunted.

Flash Point: N/D

Flammable Limits: None, Explosive Device

Auto-Ignition Temperature: 225° F

Extinguishing Media: Dry, Chemical Extinguisher

Special Fire-Fighting Procedures: None.

Grounding Procedure: Insure that the device is shunted and handlers are

grounded.

Stability Considerations: None

Incompatibility: Shock, Flame, Friction, Temperature high heat and

static sources.

Hazardous decomposition products: None

Hazardous products of combustion: Flame, high heat, carbon monoxide, carbon

dioxide, oxides of nitrogen, hydrogen chloride, trace cyanide compounds, oxides and salts of lead. Under certain conditions, device can propel high

velocity particles on initiation.

Hazardous Polymerization: None

V. HEALTH HAZARD DATA

Emergency and First Aid Procedure:

Treat burns and any laceration by cleaning and applying sterile bandages. Transport individual for further medical treatment.

Primary Route of Entry: N/A (cartridge is intact)

Inhalation of actuation fumes.

Cancer Information: Not listed as carcinogen by N.T.P. if cartridge is

intact

Reported effects on Humans: Respiratory irritant.

Other: N/A (cartridge is intact)

CARTRIDGE ACTUATED DEVICES, INC. 51 Dwight Place, Fairfield, New Jersey 07004

074055 26 AUG 04 page 3 of 3

VI. SPILL AND LEAK PROCEDURES

Steps to be taken if material is spilled: (applies only if cartridge is ruptured)
Clean spill after liberally wetting down with solvent (Acetone, Butyl Acetate or Alcohol) by wiping material up with paper towels or with cotton rag. Keep a fire extinguisher present. Wear safety glasses, protective gloves, and non-static generating clothing during clean up or transfer operation.

Waste Disposal Method:

Disposal must be in accordance with local, state, and Federal regulations.

VII. APPLICABLE CONTROL MEASURES

Appropriate Hygienic Practices: N/A

Personal Protective Equipment: Safety glasses & grounding devices (ground straps and/or

conductive footwear). When firefighting, wear

NIOSH approved gas respirator.

Work Practices: Avoid high temperatures; keep the cartridge

shunted and wear personal protective equipment.

Work behind shielding.

Handling and Storage precaution: Recommended storage, 70°F

Engineering Controls: Work with device in a shielded area, keep shunted

until installed.

Protective Measures during Repair and Maintenance:

Eliminate static discharge sources. Avoid flame

or high heat. Shield the device when working

with the device.

DISCLAIMER: The above information was taken from various published and unpublished sources

and is believed to be accurate and to represent the best information currently available to us. However, we make no warranty, expressed or implied, of the accuracy of such information, and assume no liability resulting from its use. Users should make their own investigation to determine suitability of the information for their particular

purposes.

THIS UNIT IS NOT USER SERVICEABLE. DO NOT ATTEMPT DOWNLOADING OR DISASSEMBLING.

Net Reactive Material Content: 1.5 grams maximum per unit.